

Iwatsu ADIX Integration System Compatibility Information

TELEPHONE SYSTEM	
Software Requirements	Versions 4.2 and 5.2
End-to-End DTMF, Station	Yes
End-to-End DTMF, Console	Yes
Overflow to Operator from CallXpress	Yes
PBX Disconnect Code	Yes (see 1 below)
AVT INTEGRATION TYPE	
	In-Band
MODULES SUPPORTED	
Automated Attendant	Yes
Voice Mail	Yes
Faxtext	Yes
Fax Mail	Yes
Networking	Yes
AUTOMATED ATTENDANT	
Blind Transfer	Yes
Monitored Transfer	Yes
T-Transfer	Yes
Confirmed Transfer	Yes
Call Screening	Yes (see <i>Screening</i> below)
Caller Queuing	Yes (see <i>Queuing</i> below)
Operator Overflow to CallXpress	Yes
CO Trunk ID	Yes
VOICE MAIL	
Callouts/Message Notification	Yes
Set MWI	Yes
Cancel MWI	Yes
Call Forward to Personal Greeting	Yes
Automatic Subscriber Logon	Yes

¹ Loop current disconnect with IX-8SUBS-1 card or 55** with standard line cards.

Screening: Not compatible with blind transfers, or transfer actions that use *, #, or 0 to prefix the extension number.

Queuing: Not compatible with blind transfers.

TELEPHONE SYSTEM HARDWARE NOTES

Single-line station ports (one per CallXpress port) P/N IX-8SUBS
See Iwatsu ADIX Technical Installation Procedure (P/N 081-00514-00)